

Refrigerator Vans



1300 Nord Avenue, Chico, CA 95926 • (866) 892-0150 • www.NorCalVans.com

REFRIGERATOR OPTIONS



Diamondplate Floors
Upgrade and add 12"-16" Sides



E Track - Make sure
your cargo is secure



Security Cameras



Voltaair TRU Equipment Monitoring - Real
time Alarms, Optimized, Efficient
GPS, and Fast Support



Vanco van liners are built of prefabricated
panels so they can be removed to repair
collision damages.



Curbside Entry for
quick access into cab

PLUTO - ELECTRIC REEFER UNIT SPECS

Refrigeration Units Model	Pluto	Pluto +
Working Voltage	12V	12V
Refrigerant – R134a	(2.6 lbs.)	(3.2 lbs.)
Cooling Capacity		
+15C (60F)	3300 W (10560 BTU/H)	4100 W (12800 BTU/H)
+5C (41F)	2700 W (8640 BTU/H)	3600 W (11580 BTU/H)
-15C (5F)	1100 W (3800 BTU/H)	2100 W (4800 BTU/H)
Heating and Defrost	Hot Gas Heating	
Heating Capacity	1400 W (3400 BTU/H)	1800 W (5100 BTU/H)
Compressor Type	12V DC Brushless Electrical	24V DC Brushless Electrical
Evaporator Air Volume	>1050m ³ /h (618 CFM)	>380 m ³ /h (810 CFM)
Average Current	12V 65A	12V 92A
Max Current	12V 85A	12V 122A
Condenser Dimensions	1100 x 800 x 217 mm (43.3 x 32.8 x 8.5 in)	
Condenser Weight	30 kg (66 lbs.)	35 kg (77 lbs.)
Evaporator Dimension	766 x 530 x 153 mm (30.2 x 20.9 x 6 in)	